



# STING





best sprayer- top of quality  
LT 300 - LT 400



# Standard equipment

Model	Tank in high density polyethylene
Sting.300	Lt. 300
Sting.400	Lt.400

## Technical data: components

Model	Power required $\geq$ 	Fan 	Low pressure pump [Optional]	Centrifugal pump 	Litre-counter dispensers 
Sting	CV 45 - 33 KW	Diameter 500mm 11750 m <sup>3</sup> /hr	Maximum flow 135lt/min Maximum pressure 20 bar	Maximum flow 200lt/min Maximum pressure 6 bar	0-800 lt/min





## Technical data: sprayer's measures

MODEL	minimum height	standard height	variable height	width	length	weight
Sting 50	130 cm	230 cm	-	100 cm	150 cm	260 kg

## Sting: accessories on request ordered and installed at the origin

ACCESS.52	Universal joint cv 60-700 mm
ACCESS.EL	Electrostatic system for the positive charge of the treatment flow
OMOLOGAZIONE.POWER	Classification for road circulation, full load, with direct coupling to the tractor (special drawbar, lights, foot rest, license plate holder)

# Sting: distribution devices

	<p><b>2V.ST</b></p>	<p>2 lower fans (8 sectors in stainless steel)</p>
	<p><b>2C2V.ST</b></p>	<p>2 upper guns 2 lower fans (8 sectors in stainless steel)</p>
	<p><b>4V.ST</b></p>	<p>2 upper fans (8 sectors in stainless steel) 2 lower fans (8 sectors in stainless steel)</p>
	<p><b>3T.ST</b>  <b>3TG.ST</b></p>	<p>Hydraulic vertical movement gun with 3 dispensers and hydraulic lines  Hydraulic vertical and swivel movement gun 200 with 3 dispensers and hydraulic lines</p>